



COMPLETE GASOLINE TREATMENT



- *Maximizes power & fuel efficiency*
- *Cleans fuel system components*
- *Prevents ethanol related problems*

Complete Gasoline Treatment

Woolsey® Complete Gasoline Treatment is formulated with sophisticated additives to keep the engine & fuel system in like new condition. Continued use can maximize power, improve fuel economy, lower maintenance costs, and reduce harmful exhaust emissions.

With it's unique formulation, Woolsey Complete Gasoline Treatment provides outstanding performance and maximum protection. It consists of special additives and inhibitors to coat and protect the entire fuel system against corrosion and the harmful effects of ethanol, in addition to dispersants that break down contaminants and excess water to prevent phase separation. This proprietary solution also consists of an exceptional detergent package that cleans performance hindering deposits from valves and injectors, and powerful antioxidants that extend the gasoline shelf life for up to two years during seasonal storage.

Applications

This high performance gasoline additive is a very effective multifunctional treatment that can be used to maximize the performance and shelf life of gasoline. It can be easily blended into all types of gasoline and is formulated for use in all types of 2 & 4 cycle gasoline engines and applications. This includes passenger, heavyduty, high performance, marine, agriculture, motorcycle, lawn equipment, stand-by generators & other gasoline engines. This premium product may be used in all automotive & other gasoline engines where improved performance, corrosion protection and longer shelf life of fuel is desired.

NOTE: This product does not replace the need for 2-cycle oil.

TECHNICAL INFORMATION

Color (ASTM D1544)	5
Specific Gravity @ 60°F	0.8750
Density, lbs./gal. (approx.)	7.29
Flash Point °F, PMCC	105
Additive Pour Point °F	<-50
Viscosity @ 77°F cSt	N/A

Blending Recommendations

This product should be added to the fuel storage tank prior to adding fuel. Storage tank should have a 20% heel of gasoline & be free of excess water and/or sludge.

Treat Rate: 1oz : 5 gallons; 8oz : 40 gallons

Safety Precautions

When handling this product, persons should exercise caution and wear protective goggles, gloves and clothing. See cautions indicated in the corresponding Safety Data Sheet before handling and storing this product.

Warranty

We guarantee this product to comply with our published specifications. Since the use of this product is beyond our control, we disclaim responsibility for its performance, handling, use, storage, the results obtained, or any injury of any nature resulting there from. Product warrantee and seller's obligations apply only to replacement of product. Seller assumes no liability for any claim or loss of any other kind. In no event shall seller be liable for indirect punitive, special or consequential damages or expenses. Any warrantee claim shall be governed by and construed in accordance with the laws and jurisdiction of the State of North Carolina.