



DIESEL PERFORMANCE ENHANCER



- *Restores lost fuel economy & power*
- *Stabilizes fuel & prevents sludge*
- *Cleans all fuel injectors*

Diesel Performance Enhancer

Woolsey® Diesel Performance Enhancer is formulated to remove and prevent fuel system deposits and corrosion, improve lubricity and cetane, and extend the shelf life up to two years.

Woolsey Diesel Performance Enhancer contains a unique detergent package that removes and prevents all types of deposits in injectors, combustion chambers and fuel filters, improving fuel economy, while restoring and maximizing engine performance. Advanced corrosion inhibitors and lubricity improvers work together to coat and protect the entire fuel system against rust and premature wear which reduces downtime and lowers maintenance costs. The addition of cetane improver reduces black smoke, provides easier starts and faster warm-ups along with a boost of up to three numbers. Powerful stabilizers protect from high temperature degradation, reduce sludge formation and extends the shelf life for up to two years during seasonal storage.

This product's advanced technology can also be used in biodiesel blends to treat and prevent all the associated issues created by biodiesel. Biodiesel is harder to treat due to different wax packages, cold weather operation issues and higher water content.

Applications

This diesel additive can be used to improve the quality of high sulfur, low sulfur, ultra-low sulfur and biodiesel blended fuels. Typical applications include fleet, farm, marine, power generation, construction, and all other heavy-duty diesel applications.

NOTE: Woolsey Diesel Performance Enhancer contains no alcohol and meets ultra-low sulfur diesel requirements.

TECHNICAL INFORMATION

Color (ASTM D1544)5

Specific Gravity @ 68° F 0.8946

Density, lbs./gal. (calculated)7.47

Flash Point °F, TCC127

Additive Pour Point °F..... <-50

Viscosity @ 70°F cP.....4.62

The sulfur content of this diesel fuel additive does not exceed 15 ppm

Blending Recommendations

This product should be added to the fuel storage tank prior to adding fuel. Storage tank should have a 20% heel of gasoline & be free of excess water and/or sludge.

Treat Rate: 8oz : 60 gallons - Keep Clean/Cleanup
 8oz : 30 gallons - Faster Cleanup

Safety Precautions

When handling this product, persons should exercise caution and wear protective goggles, gloves and clothing. See cautions indicated in the corresponding Safety Data Sheet before handling and storing this product.

Warranty

We guarantee this product to comply with our published specifications. Since the use of this product is beyond our control, we disclaim responsibility for its performance, handling, use, storage, the results obtained, or any injury of any nature resulting there from. Product warrantee and seller's obligations apply only to replacement of product. Seller assumes no liability for any claim or loss of any other kind. In no event shall seller be liable for indirect punitive, special or consequential damages or expenses. Any warrantee claim shall be governed by and construed in accordance with the laws and jurisdiction of the State of North Carolina.